

Thuyết minh thông số kỹ thuật Switch Aruba Instant On 1930 JL683A



Performance & Bandwidth thông số JL683A Switch - L3 - managed - 24 x 10/100/1000 (PoE) + 4 x 1 Gigabit / 10 Gigabit SFP+ - rack-mountable - PoE (195 W)	
Mã	JL683A
Product Description	HPE Aruba Instant On 1930 24G Class4 PoE 4SFP/SFP+ 195W Switch - switch - 28 ports - managed - rack-mountable
Device Type	Switch - 28 ports - L3 - managed
Enclosure Type	Rack-mountable 1U
Subtype	Gigabit Ethernet
Ports	24 x 10/100/1000 (PoE) + 4 x 1 Gigabit / 10 Gigabit SFP+
Power Over Ethernet (PoE)	PoE
PoE Budget	195 W
Performance	Switching capacity: 128 Gbps Throughput: 95.23 Mpps Latency (1 Gbps): 2.4 µs Latency (10 Gbps): 1.3 µs
Capacity	Link aggregation ports: 8 IPv4 routes (static): 32 VLANs supported: 256 Access Control Entries (ACEs) per ACL: 480 Packet buffer size: 1.5 MB
MAC Address Table Size	16000 entries
Jumbo Frame Support	9216 bytes
Routing Protocol	Static IP routing
Remote Management Protocol	SNMP 1, RMON, SNMP 3, SNMP 2c, HTTP, HTTPS, TFTP, RADIUS
Features	Flow control, DHCP support, ARP support, VLAN support, auto-uplink (auto MDI/MDI-X), IGMP snooping, IPv6 support, half duplex mode, full duplex mode, Spanning Tree Protocol (STP) support, Multiple Spanning Tree Protocol (MSTP) support, Access Control List (ACL) support, Quality of Service (QoS), Trusted Platform Module (TPM), LLDP support, Link Aggregation Control Protocol (LACP), Energy Efficient Ethernet, Class of Service (CoS), BPDU Filter, PoE Class 4
Compliant Standards	IEEE 802.3, IEEE 802.3u, IEEE 802.1D, IEEE 802.1Q, IEEE 802.3ab, IEEE 802.1p, IEEE 802.3af, IEEE 802.3x, IEEE 802.3ad (LACP), IEEE 802.1w, IEEE 802.1x, IEEE 802.1s, IEEE 802.1ab (LLDP), IEEE 802.3at, IEEE 802.3az, IEEE 802.2af
Power	AC 120/230 V (50/60 Hz)
Dimensions (WxDxH)	17.4 in x 10.4 in x 1.7 in
Weight	7.72 lbs