

Thuyết minh thông số kỹ thuật Switch L3 Cisco CBS350-16T-2G-EU

Mô tả	Cisco CBS350-16T-2G-EU L3-Managed Gigabit Switch 16 Port Gigabit, 2 Port SFP ,VLAN, Spanning Tree Protocol (STP), Advanced Threat Protection, IPv6 first-hop security, Quality Of Service (QoS), sFlow, IPv4/IPv6 static routing
Capacity in millions of packets per second (mpps) (64-byte packets)	26.78 mpps
Switching capacity in gigabits per second (Gbps)	36 Gbps
Ports	
RJ-45 Ports	16
Combo Ports(RJ 45 + Small form-factor pluggable [SFP])	2
Console port	Cisco Standard mini USB Type-B / RJ45 console port
USB slot	USB Type-A slot on the front panel of the switch for easy file and image management
Buttons	Reset button
Cabling type	Unshielded Twisted Pair (UTP) Category 5e or better for 1000BASE-T
LEDs	System, Link/Act, PoE, Speed
Flash	256 MB
CPU	800 MHz ARM
DRAM	512 MB
Packet buffer	1.5 MB
Unit dimensions (W x H x D)	268 x 272 x 44 mm (10.56 x 10.69 x 1.73 in)
Unit Weight	1.78 kg (3.92 lb)
Certification	UL (UL 60950), CSA (CSA 22.2), CE mark, FCC Part 15 (CFR 47) Class A
Operating temperature	23° to 122°F (-5° to 50°C)
Storage temperature	-13° to 158°F (-25° to 70°C)
Operating humidity	10% to 90%, relative, noncondensing
Storage humidity	10% to 90%, relative, noncondensing
Package Contents	Cisco Business 350 Series Managed Switch
	Power Cord (Power adapter for select 8-port and 16-port SKUs)
	Mounting Kit
	Quick Start Guide