

Thuyết minh thông số kỹ thuật thiết bị hội nghị Cisco CS-KIT-K9

Mã	CS-KIT-K9
Product Description	Cisco Spark Room Kit - video conferencing kit - with Touch10
Device Type	Video conferencing kit
VoIP Protocols	H.323, SIP
Codec	G.711, G.722, G.729, G.722.1, AAC-LD, Opus
Digital Signaling Protocol	H.323, SIP, H.239, BFCP
Data Compression Protocol	H.264
Features	DTMF decoding
Networking	Ethernet, Fast Ethernet, Gigabit Ethernet, IEEE 802.11b, IEEE 802.11a, IEEE 802.11g, IEEE 802.11n, Bluetooth 4.0, IEEE 802.11ac
Power	AC 120/230 V (50/60 Hz)
Bundled with	Touch10
General	
Device Type	Video conferencing kit
VoIP Protocols	H.323, SIP
Voice Codecs	G.711, G.722, G.729, G.722.1, AAC-LD, Opus
Quality of Service	IEEE 802.1Q (VLAN), IEEE 802.1p
IP Address Assignment	DHCP
Security	IEEE 802.1X, H.235 v3
Built-in Devices	Microphone, stereo speakers, camera
Bundled with	Touch10
Expansion / Connectivity	
Interfaces	2 x display / video - HDMI output - 19 pin HDMI Type A ; 1 x display / video - HDMI input - 19 pin HDMI Type A ; 2 x network - RJ-45 ; 1 x USB - 5 pin Micro-USB Type A ; 1 x USB - 4 pin USB Type A ; 2 x microphone - input ; 1 x audio - output
Manufacturer Warranty	
Service & Support	Limited warranty - 90 days
Miscellaneous	
Cables Included	1 x HDMI cable ; 2 x network cable - 16.4 ft ; 1 x network cable - 26 ft
Mounting Kit	Included
Compliant Standards	AES, RoHS, WEEE, Directive 53/2014/EU, Directive 2014/35/EU, Directive 2014/30/EU
Networking	
Connectivity Technology	Wireless, wired
Data Link Protocol	Ethernet, Fast Ethernet, Gigabit Ethernet, IEEE 802.11b, IEEE 802.11a, IEEE 802.11g, IEEE 802.11n, Bluetooth 4.0, IEEE 802.11ac
Features	IPv6 support, wall mountable, Quality of Service (QoS), reset button, 4K resolution support, automatic gain control (AGC), AES encryption, Network Timing Protocol (NTP)
Power	
Power Device	Power supply - external
Voltage Required	AC 120/230 V (50/60 Hz)
Environmental Parameters	
Min Operating Temperature	32 °F
Max Operating Temperature	104 °F
Humidity Range Operating	10 - 90%

Modem	
Digital Signaling Protocol	H.323, SIP, H.239, BFCP
Data Compression Protocol	H.264
Features	DTMF decoding
Video Input	
Digital Video Capture Resolution	3840 x 2160, 1080p
Video Output	
Supported Display Graphics	HDTV (1920x1080), UHD (3840 x 2160)