

Thuyết minh thông số kỹ thuật thiết bị hội nghị Cisco CS-KITPLUS-K9

Mã	CS-KITPLUS-K9
Product Description	Cisco Spark Room Kit Plus - GPL - video conferencing kit
Device Type	Video conferencing kit
VoIP Protocols	H.323
Codec	H.264, G.711, G.722, G.729, G.722.1, AAC-LD, Opus
Digital Signaling Protocol	H.323, SIP, H.460.18, H.460.19, BFCP
Data Compression Protocol	H.264
Features	DTMF decoding
Video Input	Digital video camera - HDMI
Audio Input	6 microphones
Audio Output	Speaker(s)
Input Device	10" touchscreen
Networking	Ethernet, Fast Ethernet, Gigabit Ethernet, IEEE 802.11b, IEEE 802.11a, IEEE 802.11g, IEEE 802.11n, Bluetooth 4.0, IEEE 802.11ac
Power	AC 120/230 V (50/60 Hz)
General	
Device Type	Video conferencing kit
VoIP Protocols	H.323
Voice Codecs	G.711, G.722, G.729, G.722.1, AAC-LD, Opus
Video Codecs	H.264
Quality of Service	IEEE 802.1Q (VLAN), Differentiated Services (DiffServ), IEEE 802.1p
IP Address Assignment	DHCP
Security	IEEE 802.1X, H.235 v3
Network Protocols	HTTP, DNS, HTTPS, NTP
Dimensions & Weight Details	Camera - Width 37.4 in Depth 4.1 in Height 4.7 in Weight 10.6 lbs Main system - Width 14.1 in Depth 5.6 in Height 1.7 in Weight 3.9 lbs
Expansion / Connectivity	
Interfaces	2 x display / video - HDMI input - 19 pin HDMI Type A 1 x display / video - HDMI input - 19 pin HDMI Type A 2 x display / video - HDMI output - 19 pin HDMI Type A 1 x audio - output - mini-phone stereo 3.5 mm 1 x audio - output - RCA 3 x audio - input - mini-phone 3.5 mm 3 x network - RJ-45 1 x USB 2.0
Manufacturer Warranty	
Service & Support	Limited warranty
Miscellaneous	
Cables Included	1 x network cable - 26 ft
Mounting Kit	Included
Compliant Standards	AES, RoHS, WEEE, CEC, Directive 2002/96/EC, Directive 2011/65/EU, FCC CFR47 Part 15 B Class A, Directive 2014/35/EU, Directive 2014/30/EU, Directive 2014/53/EU
Networking	
Connectivity Technology	Wireless, wired
Data Link Protocol	Ethernet, Fast Ethernet, Gigabit Ethernet, IEEE 802.11b, IEEE 802.11a, IEEE 802.11g, IEEE 802.11n, Bluetooth 4.0, IEEE 802.11ac
Network / Transport Protocol	NTP, DHCP, DNS
Features	DiffServ support, wall mountable, Quality of Service (QoS), SSH support, Audio Return Channel (ARC), 4K resolution support, security lock slot (cable lock sold separately), automatic gain control (AGC), 802.1x authentication, URI Dialing, administrator's password
Compliant Standards	IEEE 802.1Q, IEEE 802.1p, IEEE 802.1x
Power	

Power Device	Power supply - external
Voltage Required	AC 120/230 V (50/60 Hz)
Power Consumption Operational	70 Watt
Environmental Parameters	
Min Operating Temperature	32 °F
Max Operating Temperature	95 °F
Humidity Range Operating	10 - 90%
Audio Output	
Type	Speaker(s)
Frequency Response	70 - 20000 Hz
Audio Input	
Type	6 microphones - integrated
Input Device	
Type	10" touchscreen
Modem	
Digital Signaling Protocol	H.323, SIP, H.460.18, H.460.19, BFCP
Data Compression Protocol	H.264
Features	DTMF decoding
Video Input	
Type	Digital video camera (color) - external
Interface Type	HDMI
Digital Video Capture Resolution	3840 x 2160, 1080p
Video Output	
Supported Display Graphics	UHD (3840 x 2160)
Digital Video Standard	High-Definition Multimedia Interface (HDMI)