

Thuyết minh thông số kỹ thuật Power Supply Cisco PWR-C1-1100WAC-P

Performance & Bandwidth thông số thiết bị nguồn cho Switch Cisco Catalyst 9300 PWR-C1-1100WAC-P/2 Cisco Catalyst 9300 1100W AC Power Supply	
Mã	PWR-C1-1100WAC-P=, PWR-C1-1100WAC-P/2, PWR-C1-1100WAC, PWR-C1-1100WAC/2
Product Description	Cisco Config 1 Secondary Power Supply - power supply - hot-plug / redundant - 1100 Watt
Device Type	Power supply - hot-plug / redundant - plug-in module
80 PLUS Certification	80 PLUS Platinum
Weight	3.09 lbs
Input Voltage	AC 115-240 V
Output Voltage	-56 V
Power Capacity	1100 Watt
Input Connectors	Power IEC 60320 C16
Dimensions (WxDxH)	3.3 in x 11.7 in x 1.4 in
Designed For	P/N: C9300-24H-10A, C9300-24H-10E, C9300-24H-1E, C9300-48UXM-A-CAP, C9300L-24P-4X-10A, C9300L-24P-4X-10E, C9300L-24T-4G-10A, C9300L-24T-4G-10E, C9300L-24T-4X-10E, C9300L-24UXG2Q-10A, C9300L-24UXG2Q-10E, C9300L-24UXG2Q-1A, C9300L-24UXG4X-10E, C9300L-24UXG4X-1E, C9300L-48P-4X-E-WS, C9300L-48UXG4X-CAP
General	
Device Type	Power supply - hot-plug / redundant - plug-in module
Miscellaneous	
Features	LED indicators
Compliant Standards	TUV GS, CISPR 22 Class A, CISPR 24, cUL, EN55024, EN55022 Class A, CISPR 22, CCC, EMC, RoHS, UL 60950-1, IEC 60950-1, KCC, FCC Part 15 A, AS/NZS, VCCI Class A, CAN/CSA-C22.2 No. 60950-1
Environmental Parameters	
Min Operating Temperature	23 °F
Max Operating Temperature	113 °F
Humidity Range Operating	10 - 95% (non-condensing)
Sound Emission	48 dBA
Power Device	
Input Voltage	AC 115-240 V
Frequency Required	50 - 60 Hz
Input Connectors	Power IEC 60320 C16
Output Voltage	-56 V
Power Capacity	1100 Watt
80 PLUS Certification	80 PLUS Platinum
Dimensions & Weight	
Width	3.3 in
Depth	11.7 in
Height	1.4 in
Weight	3.09 lbs
Compatibility Information	

Designed For	P/N: C9300-24H-10A, C9300-24H-10E, C9300-24H-1A, C9300-24H-1E, C9300-24H-A, C9300-24H-E, C9300-24H-EDU, C9300-24P-P, C9300-24T-P, C9300-24U-A-UL, C9300-24UB-A, C9300-24UB-E, C9300-24U-E-UL, C9300-24U-P, C9300-24UX-A-WS, C9300-24UXB-A, C9300-24UXB-E, C9300-24UX-E-WS, C9300-24UX-P, C9300-48H-1A, C9300-48H-A, C9300-48H-E, C9300-48H-EDU, C9300-48S-EDU, C9300-48S-E-RF, C9300-48T-10A, C9300-48U-10A, C9300-48U-A-UL, C9300-48U-A-WS, C9300-48UB-A, C9300-48UB-E, C9300-48U-E-UL, C9300-48UXM-A-CAP, C9300-96S-BUN, C9300L-24P-4G-1A, C9300L-24P-4G-1E, C9300L-24P-4X-10A, C9300L-24P-4X-10E, C9300L-24P-4X-1A, C9300L-24T-4G-10A, C9300L-24T-4G-10E, C9300L-24T-4G-1E, C9300L-24T-4G-E-RF, C9300L-24T-4X-10A, C9300L-24T-4X-10E, C9300L-24T-4X-1A, C9300L-24T-4X-1E, C9300L-24T-4X-A-RF, C9300L-24UXG2Q-10A, C9300L-24UXG2Q-10E, C9300L-24UXG2Q-1A, C9300L-24UXG2Q-1E, C9300L-24UXG-2Q-A, C9300L-24UXG-2Q-E, C9300L-24UXG2Q-EDU, C9300L-24UXG4X-10A, C9300L-24UXG4X-10E, C9300L-24UXG4X-1A, C9300L-24UXG4X-1E, C9300L-24UXG-4X-A, C9300L-24UXG-4X-E, C9300L-24UXG4X-EDU, C9300L-48P-4G-10A, C9300L-48P-4G-10E, C9300L-48P-4G-1A, C9300L-48P-4G-1E, C9300L-48P-4X-10A, C9300L-48P-4X-10E, C9300L-48P-4X-E-WS, C9300L-48PF-4G-10A, C9300L-48PF-4G-10E, C9300L-48PF-4G-1A, C9300L-48PF-4G-1E, C9300L-48PF-4G-A, C9300L-48PF-4G-E, C9300L-48PF-4G-EDU, C9300L-48PF-4X-10A, C9300L-48PF-4X-10E, C9300L-48PF-4X-1A, C9300L-48PF-4X-1E, C9300L-48PF-4X-A, C9300L-48PF-4X-E, C9300L-48PF-4X-EDU, C9300L-48T-4G-10A, C9300L-48T-4G-1A, C9300L-48T-4G-1E, C9300L-48T-4G-E-RF, C9300L-48T-4X-10A, C9300L-48T-4X-10E, C9300L-48T-4X-1A, C9300L-48UXG2Q-10A, C9300L-48UXG2Q-10E, C9300L-48UXG2Q-1A, C9300L-48UXG2Q-1E, C9300L-48UXG-2Q-A, C9300L-48UXG-2Q-E, C9300L-48UXG2Q-EDU, C9300L-48UXG4X-10A, C9300L-48UXG4X-10E, C9300L-48UXG4X-1A, C9300L-48UXG4X-1E, C9300L-48UXG-4X-A, C9300L-48UXG4X-CAP, C9300L-48UXG-4X-E, C9300L-48UXG4X-EDU, C9300L-48UXG4XE-RF, C9300X-12Y-A, C9300X-12Y-E, C9300X-24Y-A, C9300X-24Y-E
--------------	--