

## Thuyết minh thông số kỹ thuật Power Supply Cisco PWR-C5-1KWAC/2

Performance & Bandwidth thông số thiết bị nguồn cho Switch Cisco Catalyst 9200L PWR-C5-1KWAC/2 Cisco Catalyst 9200L 1000W AC Power Supply	
Mã	PWR-C5-1KWAC, PWR-C5-1KWAC=, PWR-C5-1KWAC/2
Product Description	Cisco Config 5 Secondary Power Supply - power supply - hot-plug / redundant - 1000 Watt
Device Type	Power supply - hot-plug / redundant - plug-in module
Weight	31.74 oz
Input Voltage	AC 100-240 V
Output Voltage	54 V
Power Capacity	1000 Watt
Input Connectors	Power IEC 60320 C16
Dimensions (WxDxH)	4 in x 7.6 in x 1.6 in
Designed For	P/N: C9200-48PXG-A, C9200-48PXG-A++, C9200-48PXG-E, C9200-48PXG-E++, C9200L-48P-4G-10A, C9200L-48P-4G-10E, C9200L-48P-4X-E-WS, C9200L-48P-4X-RE, C9200L-48PXG-2Y-1A, C9200L-48PXG-2Y-1E, C9200L-48PXG-2YE++, C9200L-48PXG-4X-1A, C9200L-48PXG-4X-1E, C9200L-48PXG-4XA++, C9200L-48PXG-4XE++
General	
Device Type	Power supply - hot-plug / redundant - plug-in module
Miscellaneous	
Compliant Standards	EN 61000-3-2, EN 61000-3-3, EN55024, EN 61000-6-1, CCC, ICES-003 Class A, UL 60950-1, IEC 60950-1, EN 60950-1, AS/NZS 3548 Class A, BSMI Class A, VCCI Class A, FCC CFR47 Part 15 B Class A, EN 300 386, EN 55032 Class A, CISPR 32 Class A, CAN/CSA-C22.2 No. 60950-1, CISPR 35
Environmental Parameters	
Min Operating Temperature	23 °F
Max Operating Temperature	113 °F
Humidity Range Operating	5 - 90% (non-condensing)
Power Device	
Input Voltage	AC 100-240 V
Frequency Required	50 - 60 Hz
Input Connectors	Power IEC 60320 C16
Output Voltage	54 V
Power Capacity	1000 Watt
Dimensions & Weight	
Width	4 in
Depth	7.6 in
Height	1.6 in
Weight	31.74 oz
Compatibility Information	
Designed For	P/N: C9200-48P-1A, C9200-48P-1E, C9200-48P-A, C9200-48P-A++, C9200-48P-E, C9200-48P-E++, C9200-48P-EDU, C9200-48PXG-A, C9200-48PXG-A++, C9200-48PXG-E, C9200-48PXG-E++, C9200L-24PXG2Y-EDU, C9200L-24PXG4X-EDU, C9200L-48P-4G-10A, C9200L-48P-4G-10E, C9200L-48P-4G-1A, C9200L-48P-4G-1E, C9200L-48P-4G-A, C9200L-48P-4G-A++, C9200L-48P-4G-A=, C9200L-48P-4G-E, C9200L-48P-4G-E++, C9200L-48P-4G-EDU, C9200L-48P-4X-1A, C9200L-48P-4X-1E, C9200L-48P-4X-A, C9200L-48P-4X-A++, C9200L-48P-4X-E, C9200L-48P-4X-E++, C9200L-48P-4X-EDU, C9200L-48P-4X-E-WS, C9200L-48P-4X-RE, C9200L-48PXG-2Y-1A, C9200L-48PXG-2Y-1E, C9200L-48PXG-2Y-A, C9200L-48PXG-2YA++, C9200L-48PXG-2Y-E, C9200L-48PXG-2YE++, C9200L-48PXG2Y-EDU, C9200L-48PXG-4X-1A, C9200L-48PXG-4X-1E, C9200L-48PXG-4X-A, C9200L-48PXG-4XA++, C9200L-48PXG-4X-E, C9200L-48PXG-4XE++, C9200L-48PXG4X-EDU